



TECHNICAL BULLETIN ULTERION[®] ASC – 60M CATIONIC SILICONE SOFTENER

PERFORMANCE FEATURES

- Full, soft hand
- Excellent drape
- Low yellowing; little effect on shades
- Compatible with most nonionic, cationic, finishing auxiliaries
- Helps to improve wrinkle resistance, tear and tensile strength

MARKET USES

- ✕ Textile Softener

Product Description

Ulterion[®] ASC – 60M is a concentrated amino-functional cationic polymer that reacts during drying to give a durable silicone finish on fibers and fabrics. *Ulterion[®] ASC – 60M* is cationic in nature and can be applied by conventional textile applications.

Product Safety

When considering the use of **Ulterion International** products, please refer to the latest Material Safety Data Sheets (MSDS). If you require an MSDS for this product; please call your **Ulterion International Representative**.

Typical Properties

Appearance:	Colorless to Slight Yellow; Hazy to Translucent Liquid
Type	Cationic Silicone Softener
pH	5.0 – 7.0
Activity	58 %

Application Methods

Recommended usage level for pad application is 0.2 to 1.5% on weight of bath to provide a luxurious hand for most fabrics. Product can also be applied via exhaust methods.



Ulterion International, LLC.
200 Tanner Drive
Taylors, SC 29687
Phone: (864) 609-0910
Fax: (864) 331-4264
www.ulterion.com

ULTERION

Taking Solutions Farther™

The information contained herein is thought to be accurate in all aspects; however, the applications for these products mentioned are presented without guarantee or responsibility as to the suitability of our products whether used singly or in combination with other products. Nothing herein is to be taken as a